

Vilariño Motorsport official Avon Motorsport Tyres Dealer. Tires for cars for circuit, hill climb, rallies, historic, sidecar... also road legal competition tires

Precios portes incluidos IVA no incluido / Prices transport included VAT not included

CROSSPLY / DIAGONALES

Sizes/Medidas	Dry/Seco	Wet/Lluvia	Rim Choice	Ideal rim	Diameter/Diametro		Section/Anchura		Tread/Banda rodadura	
	Price €	Price €	Garganta	Ideal	Ins/Pulgadas	Mm/Mm	Ins/Pulgadas	Mm/Mm	Ins/Pulgadas	Mm/Mm
6.0/16.0-10	193	211	6.0 - 7.0	6.00	16.00	407	6.50	166	5.90	151
7.0/16.0-10	197	216	7.0 - 8.0	7.00	15.90	404	7.50	190	6.80	172
8.5/16.0-10	236	256	8.5 - 9.5	9.00	15.90	403	9.25	235	8.00	203
6.5/19.5-13	202	221	5.5 - 7.0	6.00	19.25	488	6.80	173	6.30	160
7.0/19.5-13	206	226	5.5 - 8.0	6.00	19.30	490	7.10	180	6.90	175
8.0/19.5-13	219	239	7.0 - 9.0	8.00	19.30	490	8.70	221	7.90	200
8.5/19.5-13	225	245	8.0 - 10.0	8.00	19.60	497	8.90	226	8.00	203
9.0/19.5-13	228	249	9.0 - 11.0	9.00	19.90	505	10.50	267	9.30	236
6.2/20.0-13	209	228	5.5 - 6.5	6.00	19.90	505	7.20	183	6.10	154
6.5/20.0-13	212	231	5.5 - 7.0	6.00	20.10	510	7.30	185	6.50	165
7.0/20.0-13	215	234	6.0 - 8.0	7.00	20.10	510	8.00	203	7.40	187
7.2/20.0-13	217	237	6.0 - 8.0	8.00	20.20	513	9.00	229	7.10	180
7.5/20.0-13	222	242	6.5 - 8.5	8.00	20.25	514	9.00	229	7.70	195
8.2/20.0-13	228	248	7.0 - 9.0	9.00	19.95	506	9.75	248	8.50	215
9.0/20.0-13	235	255	8.0 - 10.0	10.00	20.00	508	10.65	271	9.20	233
10.0/20.0-13	243	264	9.0 - 11.0	10.00	19.80	502	11.10	282	10.20	259
6.0/21.0-13	213	231	5.5 - 7.0	6.00	20.50	520	7.40	188	6.20	157
6.5/21.0-13	219	237	5.5 - 7.5	7.00	20.50	520	9.00	229	6.50	165
7.0/21.0-13	225	244	6.0 - 8.0	8.00	20.60	523	9.00	229	7.20	182
7.5/21.0-13	230	249	6.5 - 8.5	8.00	20.50	520	8.50	216	7.40	187



Compound variations from ultra soft for hillclimb to hard for endurance circuit racing

Compuestos variados, desde muy blandos para montaña a muy duros para resistencia

Construction materials such as nylon, steel and kevlar

Distintos materiales, nylon, acero, o kevlar

As different constructions and applications can affect the finished dimensions of a tyre the figures are subject to change without prior notice.

La numeración de los neumáticos puede variar para un tipo sin previo aviso

[Wet designs click here](#)

[Dibujos de mojado, click aquí](#)

[Fitment guide](#)

[Sentido de montaje](#)

8.0/21.0-13	242	262	7.0 - 9.0	9.00	20.80	528.3	9.90	252	8.10	205.7
8.5/21.0-13	243	263	7.5 - 9.0	9.00	20.80	528	10.20	259	8.60	215
9.0/21.0-13	243	263	8.0 - 10.0	10.00	21.00	533	10.90	277	9.10	231
7.0/22.0-13	230	249	6.5 - 8.5	7.50	21.60	548	8.70	221	6.90	175
8.2/22.0-13	246	266	7.0 - 10.0	9.00	22.00	558	10.10	257	8.60	218
9.2/22.0-13	263	284	8.5 -10.5	10.00	22.40	568	11.10	282	9.10	231
10.0/22.0-13	270	291	9.0 - 12.0	11.00	22.10	561	11.90	302	10.30	261
10.5/23.0-13	282	304	9.5 -11.5	11.00	23.50	596	12.30	312	10.30	261
12.0/23.0-13	297	319	12.0 -14.0	13.00	23.20	589	14.50	368	12.30	312
13.0/23.0-13	304	326	13.0 - 15.0	14.00	23.25	590	15.15	385	13.00	330
14.0/23.0-13	307	330	14.0 - 15.0	14.00	23.25	590	15.55	395	13.60	345
13.0/24.5-13	314	337	13.0 - 15.0	14.00	24.30	617	15.50	394	12.50	317
15.0/26.0-13	347	371	15.0 - 18.0	16.00	25.75	654	17.75	451	15.00	381
16.2/26.0-13	351	376	16.0 - 18.0	17.00	25.80	655	18.75	476	16.30	414

6.6/19.5-14	203	221	5.5 - 7.5	6.00	20.00	508	7.20	183	6.80	172
6.5/21.0-14	218	237	5.5 - 7.0	7.00	21.40	543	7.25	184	7.60	193
7.0/21.0-14	224	243	5.5 - 8.0	7.00	21.00	533	7.30	184	7.90	200
7.0/21.5-14	229	249	5.5 - 6.0	5.50	21.90	556	7.75	197	7.00	177
10.0/21.5-14	245	266	8.5 - 11.0	11.00	22.05	560	11.97	304	9.84	250

7.0/21.5-15	229	249	5.5 - 7.5	6.00	22.10	561	7.40	188	7.00	177
7.5/21.5-15	236	256	6.0 - 8.0	6.00	22.20	563	7.80	198	7.20	182
8.0/21.5-15	241	261	6.5 - 8.5	7.50	21.80	553	8.80	224	7.80	198
8.7/21.5-15	257	277	7.5 - 9.0	8.00	22.10	561	9.70	246	8.40	213
9.5/21.5-15	263	284	8.0 - 10.0	10.00	21.85	554	10.65	271	9.50	241
10.0/21.5-15	267	288	8.5 - 11.0	10.00	21.85	554	11.00	279	10.00	254
10.7/21.5-15	279	300	9.0 - 11.0	10.00	21.85	554	11.30	287	10.60	269
8.0/22.5-15	242	262	6.5 - 7.5	7.00	22.45	570	8.95	227	7.75	196
9.0/23.3-15	257	278								
6.5/23.0-15	228	247	6.0 - 7.5	6.00	23.00	584	7.55	192	6.50	165
7.0/23.0-15	233	252	6.5 - 8.0	7.00	23.10	586	7.95	202	6.90	175
7.5/23.0-15	236	256	7.0 - 8.5	8.00	22.80	579	8.50	216	7.40	187

10.5/23.0-15	282	304	10.0 - 12.0	11.00	23.55	598	11.95	304	10.30	261
8.5/23.5-15	259	279	7.0 - 9.5	8.50	23.60	599	9.60	244	8.80	223
9.0/23.5-15	262	282	7.0 - 10.0	8.50	23.60	599	9.90	251	9.30	236
9.1/23.5-15	262	283	8.0 - 9.5	8.50	23.55	598	9.88	251	8.50	215
11.0/23.5-15	288	310	10.0 - 12.0	11.00	23.30	591	12.10	307	11.30	287
12.5/23.5-15	302	324	11.0 - 13.5	12.00	23.30	591	13.30	338	12.70	322
9.0/25.0-15	276	297	9.0 - 11.0	10.00	24.75	629	10.10	257	8.90	226
9.5/25.0-15	278	298	9.0 - 11.0	10.00	24.75	628	11.70	297	9.25	234
11.0/25.0-15	289	311	10.0 - 12.0	12.00	24.70	627	13.60	345	11.30	287
13.0/25.0-15	324	346	11.5 - 14.5	14.00	24.80	629	15.40	391	13.20	335
15.0/26.0-15	347	371	15.0 - 17.0	16.00	25.75	654	17.40	442	15.00	381
16.2/26.0-15	352	376	16.0 - 18.0	16.00	25.80	655	17.90	455	16.30	414
12.5/27.0-15	321	343	11.5 - 14.5	13.00	27.00	685	15.25	387	12.50	317
14.0/27.0-15	350	373	13.0 - 16.0	15.00	27.10	688	16.70	424	14.00	355
16.0/27.0-15	356	380	15.0 - 18.0	16.00	27.50	698	16.80	427	16.10	408

9.5/21.5-16	270	291	8.0 - 10.0	10.00	21.85	554	10.30	262	9.50	241
10.7/21.5-16	281	302	9.0 - 11.0	11.00	22.05	560	11.60	295	10.60	269
8.0/22.5-16	243	263	6.5 - 7.5	7.00	22.65	575	8.55	217	7.90	200
7.5/23.0-16	243	262	6.0 - 8.0	7.50	23.80	604	8.45	215	7.50	190
8.5/23.3-16	258	278	7.5 - 8.0	8.00	23.55	598	9.60	244	8.80	223
8.0/23.5-16	261	281	7.0 - 9.0	8.00	23.70	601	9.00	229	7.80	198
9.0/23.5-16	271	291	8.0 - 9.0	8.00	23.70	601	9.90	251	9.30	236
9.5/23.5-16	272	292	8.5 - 10.5	8.50	23.60	599	9.80	249	9.50	241
10.0/23.5-16	278	299	9.0 - 11.0	10.00	23.60	599	10.95	278	10.00	254
11.0/23.5-16	289	311	10.0 - 11.5	11.00	23.60	599	11.80	300	10.45	265
12.5/23.5-16	302	324	10.0 - 12.0	12.00	23.50	596	12.55	319	11.30	287
11.0/25.0-16	290	312	11.5 - 13.5	13.50	23.40	594	13.75	349	12.70	322
12.5/25.0-16	315	337	11.5 - 13.5	13.00	24.75	628	14.20	361	12.50	317
13.5/25.0-16	325	348	12.0 - 14.5	14.00	25.00	635	15.20	386	13.40	340
12.5/27.0-16	320	341								
13.2/27.0-16	324	346								
14.0/27.0-16	351	374	13.0 - 16.0	14.00	27.20	690	15.75	400	14.00	355

7.5/24.0-17	265	7.0 - 8.0	8.00	24.30	618	9.05	230	7.70	195
8.0/24.0-17	267	7.5 - 8.5	8.00	24.50	622	9.45	240	8.07	205
8.0/25.0-17	267	8.0 - 9.0	8.00	25.20	640	9.00	229	8.00	203
9.0/25.0-17	276	8.0 - 10.0	8.50	25.15	638	9.80	249	8.50	215
10.5/25.0-17	294								

RADIALS / RADIALES

Sizes/Medidas	Dry/Seco Price €	Wet/Lluvia Price €	Rim Choice Garganta	Ideal rim Ideal	Diameter/Diametro Ins/Pulgadas Mm/Mm	Section/Anchura Ins/Pulgadas Mm/Mm	Tread/Banda rodadura Ins/Pulgadas Mm/Mm
160/530R13	229	247	5.5 - 7.0	6.00	20.90 531	7.40 188	6.25 159
175/530R13	234	252	6.0 - 8.0	6.00	20.95 532	7.75 197	7.00 178
195/530R13 046	225						
195/530R13	240	259	8.0 - 9.0	8.50	20.80 528	9.70 246	8.10 207
180/550R13 A15	218		8.5 - 9.5	9.00	21.80 554	9.50 241	7.25 184
180/550R13	249	268	8.5 - 9.5	9.00	21.80 554	9.50 241	7.25 184
210/550R13 A15	225		9.0 - 10.0	10.00	21.80 554	10.60 269	8.25 210
210/550R13	258	278	9.0 - 10.0	10.00	21.80 554	10.60 269	8.25 210
230/550R13	266	286	9.0 - 11.0	10.00	21.80 554	11.40 290	9.20 234
180/565R13	258		7.0 - 10.0	7.00	22.38 568.5	8.66 220	7.20 183
200/565R13	264	283	8.0 - 10.0	8.00	22.32 567	10.20 259	9.02 215
250/570R13 A15	247		10.0 - 11.0	10.00	22.60 574	11.40 290	9.70 246
250/570R13	285	305	10.0 - 11.0	10.00	22.60 574	11.40 290	9.70 246
275/570R13	293	313	10.5 - 12.0	11.00	22.70 577	12.40 315	10.80 275
290/570R13 046	265						
290/570R13	299	320	10.5 - 12.0	11.75	22.80 579	12.48 317	11.10 282
225/600R13	296	316	10.0 - 11.0	10.50	23.75 603	11.26 286	8.25 210
245/600R13	303	323	10.0 - 11.0	10.00	23.62 600	11.30 287	9.57 243
300/600R13	325	346	13.0 - 14.0	13.00	23.90 607	14.65 272	11.85 301



Compound variations from ultra soft for hillclimb to hard for endurance circuit racing

Compuestos variados, desde muy blandos para montaña a muy duros para resistencia

Construction materials such as nylon, steel and kevlar

Distintos materiales, nylon, acero, o kevlar

As different constructions and applications can affect the finished dimensions of a tyre the figures are subject to change without prior notice.

La numeración de los neumáticos puede variar para un tipo sin previo aviso

[Wet designs click here](#)

[Dibujos de mojado, click aquí](#)

330/620R13	345	368	14.0 - 16.0	15.00	24.44	621	15.90	404	13.50	343
245/640R13	329	349	11.0 - 12.5	11.75	25.10	638	12.20	310	10.00	255
270/660R13	351	372	11.0 - 12.5	11.75	25.70	652	13.40	340	11.10	281
315/660R13	366	388	13.0 - 15.0	13.75	25.75	654	15.00	381	12.25	311
350/660R13	376	398	14.0 - 16.0	15.00	25.70	652	16.90	428	14.60	370
370/660R13	384	407	14.0 - 16.0	15.00	25.75	654	17.00	432	15.00	381
230/550R15	297	317	8.0 - 10.0	10.00	21.70	552	10.90	278	9.30	235
190/570R15	271	290	6.5 - 7.5	7.00	22.60	574	8.25	210	7.75	197
275/570R15	334	355	10.0 - 11.0	10.00	22.60	573	11.40	290	10.70	272
290/570R15	336	357	11.0 - 12.0	12.00	22.60	574	12.99	330	11.22	285
205/580R15	273	292	7.0 - 8.0	7.00	22.83	580	8.58	218	8.19	208
225/580R15	278	297	8.0 - 9.0	8.00	22.83	580	9.57	243	9.06	230
240/600R15	295	315	10.0 - 11.0	10.00	23.46	596	10.98	279	9.88	851
300/600R15	319	340	11.5-12.5	12.00	23.8	605	13.86	352	11.81	300
330/620R15	364	387	14.0 - 16.0	15.00	24.41	620	15.28	388	13.86	352
255/635R15	327	347	10.0 - 11.0	10.00	25.24	641	11.61	295	9.72	247
275/635R15	350	370	10.0 - 12.0	10.00	25.30	642	11.93	303	10.71	272
350/720R15	425	448	14.0 - 15.0	14.00	28.31	419	16.26	413	13.86	352
205/580R16	274	294	7.0 - 8.0	7.00	22.80	579	8.35	212	8.07	205
225/580R16	286	306								
210/600R16	278	298	7.0 - 8.5	7.00	23.60	599	8.60	218	8.20	210
230/600R16	292	312								
240/600R16	305	325	8.0 - 10.0	9.50	23.60	599	10.43	265	9.40	245
265/600R16	329	349	10.0 - 12.0	10.75	23.60	606	11.50	291	10.40	262
200/605R16	276	294	7.0 - 8.5	7.50	23.90	607	8.62	219	7.87	200
250/610R16	323	343								
300/610R16	344	366	10.0 - 12.0	10.75	24.30	618	12.60	319	12.50	318
325/630R16	346	368	12.0 - 13.0	12.00	25.00	635	13.30	339	12.20	311
240/650R16	340	360								
285/650R16	343	364								

[Fitment guide](#)

[Sentido de montaje](#)

200/605R17	278	296	7.0 - 8.0	8.00	24.00	609	8.70	221	7.90	201
230/605R17	295	315	8.0 - 9.0	9.00	24.00	609	9.85	250	9.20	234
205/610R17	278	296	7.0 - 8.0	8.00	24.50	622	8.50	215	7.90	201
215/610R17	282	302	7.0 - 8.0	8.00	24.30	618	9.00	229	9.00	229
210/620R17	278	298	7.0 - 8.0	7.50	24.20	615	9.00	229	8.25	210
230/620R17	302	322	8.5 - 9.5	9.00	24.38	619	9.80	249	8.99	228
250/620R17	306	326	9.5 - 10.5	10.00	24.35	618	11.00	279	10.00	254
210/635R17	282	302	7.0 - 8.0	8.00	25.00	635	9.10	230	8.10	205
285/645R17	332	353								
300/650R17	346	367								

210/640R18	324	343	TBC	8.00	25.50	648	8.94	227	8.39	213
225/640R18	327	346	8.0 - 9.0	9.00	25.50	648	10.10	257	8.80	226
240/640R18	333	353	8.5 - 9.5	9.00	25.40	645	10.80	274	9.40	239
250/640R18	340	359	9.5 - 10.5	10.00	25.40	645	11.20	284	9.90	251
260/645R18	336	357								
275/645R18	340	360	10.0 - 11.0	11,0	25,43	646	11,57	294	10,63	270
285/645R18	343	364	11.0 - 12.0	11,0	25,47	647	11,69	297	10,94	278
300/645R18	347	368	12.0 - 13.0	12,0	25,55	649	12,70	323	11,50	292
320/645R18	351	373								
335/645R18	357	379	12.5 - 13.5	12.00	25.75	654	13.30	338	13.00	330
270/650R18	350	370	10.0 - 11.0	11.00	25.80	656	11.90	302	10.70	272
300/650R18	354	374	11.0 - 12.5	12.00	25.70	653	13.00	329	12.00	304
255/660R18	354	375	10.0 - 11.0	11,0	25,98	660	10,98	279	9,76	248
270/680R18	364	385	10.5 - 11.5	11.00	26.90	683	11.75	298	10.25	260
285/680R18	368	389	11.0 - 12.0	11.00	27.00	685	11.90	302	11.00	279
300/680R18	371	392	12.0 - 13.0	12.00	26.85	682	13.00	330	12.00	305
280/705R18	353	374	11.0 - 12.0	11.00	27.80	706	12.10	307	10.85	276
300/705R18	363	384								
320/705R18	373	395	13.0 - 14.0	13.00	27.80	706	13.85	352	12.55	319
365/720R18	438	461	14.5 - 16.0	14.50	28.39	721	15.94	405	14.37	365

210/640R19	327	346	8.0 - 9.0	9	25.55	649	8.70	221	8.31	211
------------	-----	-----	-----------	---	-------	-----	------	-----	------	-----

225/640R19	330	349	7.5 - 8.5	8.5	25.5	648	9.25	235	8.98	228
240/640R19	337	357	8.5 - 9.5	9	25.5	648	9.88	251	9.37	238
250/640R19	340	360	8.5 - 10.5	9	25.35	644	10.16	258	9.76	248
270/680R19	369	390	10.5 - 11.5	10.5	26.8	681	11.46	291	10.55	268
285/680R19	373	394	11.0 - 12.0	12	26.9	683	12.87	327	11.22	285
300/680R19	374	395	12.0 - 13.0	12	26.9	683	12.99	330	11.89	302
320/705R19	376	398	13.0 - 14.0	13	27.7	704	14.09	358	12.83	326

ROAD LEGAL

ZZR		Rim Choice	Ideal rim	Diameter/Diámetro		Section/Anchura		Tread/Banda rodadura		
Sizes/Medidas	Price €	Garganta	Ideal	Ins/Pulgadas	Mm/Mm	Ins/Pulgadas	Mm/Mm	Ins/Pulgadas	Mm/Mm	
185/55R13	155	5.5 - 7.0		20.85	530	7.95	202	6.69	170	
215/55R13	165	7.0 - 8.5		22.00	559	9.06	230	7.87	200	
195/50R15	163	5.5 - 7.0		23.08	577	7.91	201	6.97	177	
205/50R15	169	6.5 - 7.5		23.48	587	8.43	214	7.72	196	
195/50R16	179	5.5 - 7.0		23.70	602	8.40	214	7.40	187	
225/45R16	191	7.0 - 8.5		24.32	608	8.86	225	7.99	203	
215/40R17	199	7.0 - 8.5		24.16	604	8.58	218	7.60	193	
225/45R17	201	7.0 - 8.5		25.34	634	8.86	225	8.27	210	
255/40R17	217	8.5 - 10.0		25.44	636	10.24	260	9.49	241	
225/40R18	213	7.5 - 9.0		25.48	637	9.06	230	7.99	203	
265/35R18	255	9.0 - 10.0		25.72	643	10.67	271	9.25	235	



Ultimate dry performance

List 1B permitted race tyre

E-marked

Full racing tread compound

Designed by Avon Tyres Motorsport Technical Dept.

Ideal championship control tyre

Tyre construction utilises materials found in GT, F3

[Tyre label for 13" ZZR](#)

[Tyre label for other ZZR](#)

[Find out more about what the EU tyre labels means.](#)

ZZS

Sizes/Medidas	Price €	Rim Choice Ideal rim		Diameter/Diámetro		Section/Anchura		Tread/Banda rodadura	
		Garganta	Ideal	Ins/Pulgadas	Mm/Mm	Ins/Pulgadas	Mm/Mm	Ins/Pulgadas	Mm/Mm
185/55R13	155	5.5 - 7.0	-	20.85	530	7.95	202	6.69	170
215/55R13	165	7.0 - 8.5	-	22.00	559	9.06	230	7.87	200
245/50R13	185	8.0 - 10.0	7.5	22.52	572	9.65	245	9.33	237
245/40R15	186	8.0 - 10.0	8.5	22.52	572	9.76	248	9.25	235
195/50R15	163	5.5 - 7.0	-	23.08	577	7.91	201	6.97	177
195/50R16	179	5.5 - 7.0	-	23.70	602	8.40	214	7.40	187
225/45R17	201	7.0 - 8.5	-	25.34	634	8.86	225	8.27	210



Fully road legal DOT marked

Complies with all EU Tyre Labeling regulations

Superb dry and wet weather performance

List 1B permitted race tyre (2015 onwards)

Full racing tread compound

Ideal championship control tyre

road legal racing tyre

Tyre construction, materials found in GT, F3, F. Ford

[View ZZS Tyre Label](#)

[Find out more about what the EU tyre labels means.](#)

CR6ZZ (Historic Rally)

Sizes/Medidas	Price €	Rim Choice Ideal rim		Diameter/Diámetro		Section/Anchura		Tread/Banda rodadura	
		Garganta	Ideal	Ins/Pulgadas	Mm/Mm	Ins/Pulgadas	Mm/Mm	Ins/Pulgadas	Mm/Mm
165/70R10	171	4.0 - 5.5	5	19.4	493	6.5	165	5.2	131
175/70R13	189	4.5 - 6.0	5	22.85	580	6.9	175	4.9	125
185/70R13	193	4.5 - 6.0	5.5	22.8	579	7.3	186	5.5	139
185/70R14	206	4.5 - 6.0	5.5	24.6	625	7.7	195	5.7	146
155R15	202	4.0 - 5.0	4.5	24.95	634	6.2	158	4.3	110
175/70R15	205	6.5 - 7.5	6.5	25	635	8.7	222	7.1	180
185/70R15	214	4.5 - 6.0	5	25.05	636	7.16	182	6.41	163
205/70R15	247	4.5 - 6.0	6	25.35	644	7.79	198	6.45	164
215/70R15	254	6.0 - 8.0	6.5	25.7	653	9.13	232	8.07	205
225/65R15	263	6.0 - 8.0	6.5	26.7	678	9.1	231	7.2	182
215/60R15	250	7.0 - 8.5	7	26.7	678	9.8	250	8.4	214
225/60R15	261	5.0 - 7.0	6	26.6	676	8.4	213	6.3	160
245/60R15	274	5.5 - 7.0	6.5	26.7	678	9	229	6.9	176
275/55R15	301	8.0 - 10.0	8.5	26.95	685	11	280	9.2	234
295/50R15	310	8.5 - 10.5	9.5	26.95	685	12	305	10	255



Road legal suitable for classic cars or racing

Confidence inspiring, wet weather performance

Classic tread pattern design

List 1B permitted race tyre

Competition tread compound

Designed specifically for classic and historic cars

Avon CR6ZZ is EXEMPT from the EU tyre labeling reg. EC1222/2009

Only to vehicles registered for the 1st time before 1 October 1990

[View exemption label](#)

CR500		Rim Choice	Ideal rim	Diameter/Diámetro		Section/Anchura		Tread/Banda rodadura	
Sizes/Medidas	Price €	Garganta	Ideal	Ins/Pulgadas	Mm/Mm	Ins/Pulgadas	Mm/Mm	Ins/Pulgadas	Mm/Mm
175/55R13	158	5.5 - 7.5	5.5	20.59	523	7.48	190	7.05	179
205/55R13	169	6.5 - 8.5	6.5	21.65	550	8.54	217	7.95	202
245/50R13	208	8.0 - 10.0	7.5	22.52	572	9.65	245	9.33	237
245/40R15	210	8.0 - 10.0	8.5	22.52	572	9.76	248	9.25	235
195/45R15	179	6.5 - 8.0	6.5	21.69	551	7.68	195	7.52	191



Staggering wet and dry performance

List 1B permitted race tyre

25 years of race tyre technology and development

Full racing tread compound

Manufactured within the motorsport manufacturing unit

Road legal racing tyre Ultra light weight construction

[View the CR500 EU tyre label](#)

[Find out more about what the EU tyre labels means](#)

ACB 10 Sport		Rim Choice	Ideal rim	Diameter/Diámetro		Section/Anchura		Tread/Banda rodadura	
Sizes/Medidas	Price €	Garganta	Ideal	Ins/Pulgadas	Mm/Mm	Ins/Pulgadas	Mm/Mm	Ins/Pulgadas	Mm/Mm
6.0/21.0-13 (185/50-13)	184	5.5 - 6.5		20.8	528	7.3	185	5.9	150
7.0/21.0-13 (195/50-13)	198	6.0 - 7.5		20.7	526	7.6	193	6.9	175
7.0/22.0-13 (215/50-13)	202	5.5 - 7.5		21.9	556	8	203	7.1	180
8.0/22.0-13 (245/45-13)	207	7.0 - 8.5		22.1	561	8.7	221	8.1	206
7.0/22.0-15 (195/45-15)	207	7.0 - 8.5		22.1	561	8.7	221	8.1	206
8.0/22.0-15 (215/40-15)	214	6.5 - 7.5		21.7	551	7.8	198	7.1	180



Avon ACB10 is EXEMPT from the EU tyre labeling reg. EC1222/2009

Only to vehicles registered for the 1st time before 1 October 1990

[View exemption label](#)

CR 28 Sport		Rim Choice	Ideal rim	Diameter/Diámetro		Section/Anchura		Tread/Banda rodadura	
Sizes/Medidas	Price €	Garganta	Ideal	Ins/Pulgadas	Mm/Mm	Ins/Pulgadas	Mm/Mm	Ins/Pulgadas	Mm/Mm
185/60R13	150	5.5 - 6.0		21.70	551	7.40	188	6.30	135
205/60R13	162	6.0 - 6.5		22.70	577	7.80	198	6.00	152
185/60R14	154	5.5 - 6.0		22.70	577	7.40	188	5.30	135
195/50R15	155	6.0 - 6.5		22.60	574	7.70	196	6.30	160



Exceptional wet weather performance

Road legal

E marked

List 1B permitted tyre

Full competition tread compound

205/50R15 158 6.5 - 7.0 23.00 584 8.60 218 7.30 185

Avon CR28 Sport is EXEMPT from the EU tyre labeling reg. EC1222/2009

Only to vehicles registered for the 1st time before 1 October 1990

[View exemption label](#)

ACB9

Sizes/Medidas Price €

5.0-22.0-13 169

6.5-23.0-13 182

Rim Choice	Ideal rim	Diameter/Diámetro		Section/Anchura		Tread/Banda rodadura	
Garganta	Ideal	Ins/Pulgadas	Mm/Mm	Ins/Pulgadas	Mm/Mm	Ins/Pulgadas	Mm/Mm
4.5-5.5		21.6	549	7.2	183	5.5	140
5.5-6.5		22.7	577	8.5	216	6.7	170



Formula Ford 1600 tyre

M+S

Sizes/Medidas Price €

160/605R15 (185/110) 167

160/640R15 (185/110) 172

170/650R15 (195/110) 172

Rim Choice	Ideal rim	Diameter/Diámetro		Section/Anchura		Tread/Banda rodadura	
Garganta	Ideal	Ins/Pulgadas	Mm/Mm	Ins/Pulgadas	Mm/Mm	Ins/Pulgadas	Mm/Mm
5.5 - 6.5	6.5	23.6	599	7.83	199	6.3	160
5.5 - 6.5	6.5	25	635	8.11	206	6.38	162
6.5 - 7.5	6.5	25.4	645	8.43	214	6.93	176



Mud and snow Rally cross tyre

ACB11

Sizes/Medidas Price €

195/580-15 235

215/580-15 256

195/580-16 244

215/580-16 256

205/620-17 259

225/640-17 275

225/640-18 281

Rim Choice	Ideal rim	Diameter/Diámetro		Section/Anchura		Tread/Banda rodadura	
Garganta	Ideal	Ins/Pulgadas	Mm/Mm	Ins/Pulgadas	Mm/Mm	Ins/Pulgadas	Mm/Mm
7.0 - 8.0	7	23.63	600	8.58	218	8.07	205
7.0 - 8.0	8	23.47	596	9.21	234	8.70	221
7.0 - 8.0	7	23.90	607	8.03	204	7.83	199
7.0 - 8.0	8	23.73	603	8.86	225	8.54	217
7.0 - 8.0	8	24.40	620	9.25	235	8.66	220
7.0 - 8.0	8	25.14	639	9.57	243	9.49	241
7.0 - 8.0	8	25.40	645	9.02	229	9.49	241



Multi Championship winning tyre
Designed for modern day Rallycross cars
Ultimate startline traction
Range of compounds available

RX WET		Rim Choice	Ideal rim	Diameter/Diámetro		Section/Anchura		Tread/Banda rodadura	
Sizes/Medidas	Price €	Garganta	Ideal	Ins/Pulgadas	Mm/Mm	Ins/Pulgadas	Mm/Mm	Ins/Pulgadas	Mm/Mm
210/635R17 (moulded)	276	7.0 - 8.0	8	25.10	638	9.53	242	8.43	214
190/570R15 (hand)	249	6.5 - 7.5	7.00	22.60	574	8.25	210	7.75	197
210/600R16 (hand)	259	7.0 - 8.5	7.00	23.60	599	8.60	218	8.20	210



AVON TYRES MOTORSPORT SIDECAR

Nylon construction

		Compound					Soft	
		Hard ←				→		
		A24	A11	A53	A27	A50	A15	A92
6.2/20.0-13	Slick Wet	9210	10595	12240	3623		2921	14227
7.2/20.0-13	Slick Wet	9116	11916	14443	3814		6583	14254
8.2/20.0-13	Slick Wet	3832	2260	12241			2555	14140
9.0/20.0-13	Slick Wet	3425	7210	12765			2553	14143
10.0/20.0-13	Slick Wet	3856	2545				4134	14251
							4134	14251

Kevlar construction

		Compound				Soft
		Hard ←			→	
		A24/514	A11	A53	A50	A15
8.2/20.0-13	Slick Inter			11206	11207	13911
9.0/20.0-13	Slick		10202	12507		
10.0/20.0-13	Slick Inter			12509	14196	
10.0/21.5-14	Slick Wet/Inter	14356	14639	14197	14196i	14268
				14197i		14268

COMPOUNDS

HARD	A70	ULTRA HARD COMPOUND FOR SALOON CAR CIRCUIT SLICK APPLICATIONS.
	A29	VERY HARD COMPOUND FOR SALOON CAR CIRCUIT SLICK APPLICATIONS.
	A60	MEDIUM COMPOUND FOR SALOON CAR CIRCUIT SLICK APPLICATIONS.
	A30	MEDIUM COMPOUND FOR CLASSIC APPLICATIONS.
	A37	HARD COMPOUND FOR SPORTSCAR, SOFT COMPOUND FOR SALOON CAR APPLICATIONS.
	A56	HARD COMPOUND FOR SPORTSCAR / SINGLE SEATER CIRCUIT SLICK.
	514	MEDIUM / HARD COMPOUND FOR SINGLE SEATER AND SPORTSCAR CIRCUIT SLICK.
	A24	MEDIUM COMPOUND FOR SINGLE SEATER, SPORTSCAR AND SIDECAR CIRCUIT SLICK APPLICATIONS.
	A11	MEDIUM COMPOUND FOR SINGLE SEATER, SPORTSCAR AND SIDECAR CIRCUIT SLICK APPLICATIONS.
	A53	SOFT COMPOUND FOR SINGLE SEATER AND SIDECAR CIRCUIT SLICK APPLICATIONS.
	A43	HARD COMPOUND FOR SINGLE SEATER CIRCUIT WET. SOFT COMPOUND FOR SPORTSCAR.
	379	HARD GT HILLCLIMB COMPOUND
	A49	MEDIUM / SOFT COMPOUND FOR RALLYCROSS, SINGLE SEATER CIRCUIT.
	A50	MEDIUM GT HILLCLIMB COMPOUND.
	A15	VERY SOFT COMPOUND FOR HILLCLIMB SLICK / WET SINGLE SEATER CIRCUIT AND SIDECAR WET APPLICATIONS.
	A92	VERY SOFT COMPOUND FOR HILLCLIMB SLICK / WET SINGLE SEATER CIRCUIT AND SIDECAR WET APPLICATIONS.
SOFT	A45	ULTRA SOFT COMPOUND FOR HILLCLIMB SLICK / WET APPLICATIONS. SPECIAL ORDER ONLY